

3. SAMPLE INSPECTION:


3.1. DESTRUCTIVE TESTING:

- 3.1.1. SELECT THREE (3) UNITS FROM LOT AND MEASURE TOTAL DCR EVERY 20°C OVER THE TEMPERATURE RANGE FROM -55°C THROUGH +125°C
- 3.1.2. CALCULATE DCA BY FOR EACH MEASUREMENT, USING EQUATION 3.2.1.1
- 3.1.3. CALCULATE, USING LINEAR REGRESSION, THE SLOPE OF THE ATTENUATION VS. TEMPERATURE CURVE
- 3.1.4. CALCULATE TCA USING THE FOLLOWING FORMULA:


$$TCA = \frac{\text{SLOPE}}{\text{ATTENUATION @ 25}^\circ\text{C}}$$

Notes on RF Testing and Circuit Layout


KTCA 16-36GHz series (for Gold Terminal type) Test Fixture




PCB Test Board




Connect test part to Test Fixture




Equipment Calibration



Room
Temperature
Test



High-Low
Temperature
Test



- 1、 S2P documents are available for download
- 2、 16-36GHz test fixture is rentable (only for Chinese customers) ,
otherwise please purchase them.


For any questions or needs, please feel free to contact inform@yantel-corp.com.

Package Outlines

All dimensions shown in mm unless stated otherwise


Unit: mm

Note: Dimension tolerance in ± 0.10 otherwise mention.



Tape & Reel Drawing


All dimensions shown in mm unless stated otherwise



Remarks:

- 1>Total tolerance of any 10 sprocket holes is $\leq \pm 0.20\text{mm}$.
- 2>The thickness is measured on the margin of carrier tape.
- 3>Carrier camber should be not more than 1mm per 100mm through a length of 250mm.
- 4>The tolerance which is not marked is $\pm 0.1\text{mm}$
- 5>A0,B0 are measured from 0.3mm above the bottom of the cavity. K0 refers to the inside depth.
- 6>The angle R which is not marked on the cavity is 0.2-0.3.
- 7>Draft angle which is not marked is 3° .
- 8>25 m/reel; 6000 units (maximum) / T&R

symbol	A0	B0	K0	P0	P	P2
spec	1.85 ± 0.1	3.2 ± 0.1	0.6 ± 0.1	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.1
symbol	W	T	E	F	D0	
spec	12.0 ± 0.3	0.3 ± 0.05	1.75 ± 0.1	5.5 ± 0.1	$\Phi 1.5^{+0.1}_{-0.0}$	



Symbol	Dimensions(mm)
A	180^{+0}_{-3}
N	60^{+1}_{-0}
W1	12.0 ± 0.3
W2	14 ± 1.0
D	25 ± 0.8
H	13 ± 0.2
E	3 ± 0.5

