


Features

- Multilayer monolithic construction yields high reliability
- Low insertion loss and small size SMD chip design
- Can simplify your complex tuning and circuit design
- LTCC process

Specifications

NO.	Parameter		SPEC		
			MIN	Typ	MAX
1	Low_Band Insertion Loss (dB)	700~2400 MHz	-	1.90 dB	2.50 dB
	High_Band Insertion Loss (dB)	2500~2700 MHz	-	2.10 dB	2.50 dB
2	Low_Band Return Loss (dB)	700~2400 MHz	10 dB	14 dB	-
	High_Band Return Loss (dB)	2500~2700 MHz	10 dB	14 dB	-
3	Low_Band Attenuation (dB)	2500~2700 MHz	10 dB	14 dB	-
		3300~4200 MHz	15 dB	18 dB	-
		4400~5000 MHz	18 dB	20 dB	-
	High_Band Attenuation (dB)	450~960 MHz	16 dB	18 dB	-
		1427~1710 MHz	16 dB	18 dB -	-
		1710~2400 MHz	10 dB	16 dB	-
4	Isolation	700~2400 MHz	15 dB	16 dB	-
		2500~2700 MHz	15 dB	15 dB	-
5	Port Impedance		50Ω		
6	Power(W)		2		

Construction



P1	GND	P4	Higher Port
P2	Common Port	P5	GND
P3	GND	P6	Low Port


Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China


Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com

Dimensions

Figure	Symbol	Dimension (mm)
	L	2.00 ± 0.15
	W	1.25 ± 0.15
	T	0.95MAX
	A	0.20 ± 0.15
	B	0.65 ± 0.15
	C	0.30 ± 0.15

Typical Electrical Characteristics (T=25°C)



Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com

