


Features

- Multilayer monolithic construction yields high reliability
- Low insertion loss and small size SMD chip design
- Can simplify your complex tuning and circuit design
- LTCC process
- Isolation resistor, external 100 ohms


Specifications

NO.	Items	Spec	Unit
1	Frequency range	5200~7700	MHz
2	Insertion Loss, above 3.0 dB	0.9 max.	dB
3	Isolation.	12 min.	dB
4	Phase Unbalance	5 max.	°
5	Amplitude Unbalance	0.5 max.	dB
6	Return Loss (Input)	9 min.	dB
7	Return Loss (Output)	10 min.	dB
Operating & Storage Condition (Component)			
Operation Temperature Range: -40°C ~ +85°C			
Storage Temperature Range: -40°C ~ +85°C			
Storage Condition before Soldering (Included packaging material)			
Storage Temperature Range: +5 ~ +40 °C			
Humidity: 30 to 70% relative humidity			


Construction & Dimensions





SUM PORT	5
PORT 1	1
PORT 1	3
GND	2、4、 6
1-3	resistor external 100 ohms



Mounting Considerations



Typical Electrical Characteristics (T=25°C)




Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com




Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com



Yantel Corporation

Add: No.308-322,3F,Building 1,Juchuang Jingu Innovation Park,Wenyuan Road 35,Xili Street,Nanshan,Shenzhen,China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com